

Specification

JACK | Shanghai stock
China No.1 | listed

Model	Needle	Needle No.	Thread No.	Needle Distance (mm)	Stitch Width (mm)	Stitch Length (mm)	Differential Ratio	Presser Foot Lifting Height (mm)	Max. Speed (s.p.m)	Volume (mm)	Weight (kg)
C5-02×250(Pocket Binding)	14#	2	4	5	—	4	0.7-2	3.5	7000	525*360*510	32/41
C5-3-02/233(Plain Seaming)	11#	1	3	—	4	4	0.7-2	5	7000	525*360*510	32/41
C5-3-32R2/223(Condense Seaming)	9#	1	3	—	1.5	4	0.7-2	5	7000	525*360*510	32/41
C5-WF-3-02/213(Nonwovens)	14#	1	3	—	4	8.5	—	5.5	7000	525*360*510	32/41
C5-4-M03/333(Plain Seaming)	11#	2	4	2	4	4.6	0.7-2	5.5	7000	525*360*510	32/41
C5-4-M03/333(Heavy Duty)	11#	2	4	2	4	4.6	0.7-2	6	7000	525*360*510	32/41
C5-MJ-4-53/233(Towel Ending)	11#	2	4	2	4	4	0.7-2	5	7000	525*360*510	32/41
C5-5-53/233(Strip Attaching)	14#	2	5	3	4	4	0.7-2	5	7000	525*360*510	32/41
C5-5-03/233(5X5 Stitch)	14#	2	5	5	5	4	0.7-2	5	7000	525*360*510	32/41
C5-5-03/333(3x4 Stitch)	14#	2	5	3	4	4	0.7-2	5	7000	525*360*510	32/41
C5-5-A04/435(Extra Heavy)	19#	2	5	5	6	5	0.8-1.5	7	7000	525*360*510	32/41
C5-5-M04/435(Demin)	19#	2	5	5	6	5	0.8-1.5	7	7000	525*360*510	32/41
C5-6-03/333(Plain Seaming)	11#	3	6	3x2	4	4	0.7-2	5	7000	525*360*510	32/41
C5-6-M04/435(Demin)	19#	3	6	5x2.5	3.5	5	0.8-1.5	7	7000	525*360*510	32/41

Note:H/M:Light and Heavy materials are good adaptability. SD is optional(start and end suction device), volume: 525×360×640(mm), weight:32/43(kg)



Light and Heavy Quick Adjustable Automatic Overlock Machine



Jack Wechat



Jack Facebook



C5 (electric)

2019.09

JACK SEWING MACHINE CO.,LTD.

No. 15 South Airport Road, Jiaojiang District, Taizhou, Zhejiang, PRC
TEL: 0086-576-88177782 88177767
FAX: 0086-576-88177787

E-mail: sales@chinajack.com
www.chinajack.com



C5(electric)

Item: Light And Heavy Quick Adjustble Automatic Overlock Machine
 Features: Suitable for light to heavy duty, Shorter remaining thread, faster



- 1 Factory Reset
- 2 Led Light
- 3 Auto Sensor
- 4 Voice Guide
- 5 Hand Wheel With Cooling Fan
- 6 USB Port



Voice guide, voice alarm easy to operate



light (mesh &Lace) Medium(knitting) Heavy(Jeans)

1 Light and Heavy Adjustable, Suitable for light to heavy duty



Though the random conversion of A-grade light material, M-grade medium and heavy material and H-grade heavy duty material by adjusting the three grades of light, medium and thick material, and meets the needs of different changing orders for such as mesh, knitting, jean, etc.



Automatic thickness detection, strong climbing ability, beautiful stitch

2 Thickness detection, strong climbing ability


At the same time, through the automatic fabric thickness detection, the motor torque is enhanced, the sewing climbing performance is improved, and the adaptability of bone cross is more smoothly realized.



Mesh sewing mode, no wrinkle, no cutting fabric.


3 Mesh sewing mode

Sewing mesh and other thin fabric through mesh sewing mode, no wrinkle, no cutting fabric.



4 Short thread remaining, no need to trim again

The unique fourth sensor patent solves the influence of factors such as the speed of gestures, and realizes the garment process requirements of the front thread (within 10mm) and the rear thread within 5mm, without secondary trimming.



5 Ultra-fast start and stop, strong power

Compared with other computerized sewing machines, shortened the comprehensive start-stop response time to 40-50%, matching 7000 rotating speed and improving the efficiency significantly. Typical case: Matching 7000 rotating speed and improving 35% efficiency significantly. Calculated worker's salary is 4000rmb per month, monthly increase of 1,400rmb.